

Part Number: 5301FE



# Security & Sound, 3 Conductor 18 AWG, BC, O/A Foil, CMR

# **Product Description**

Security & Commercial Audio Cable, Riser-CMR, 3-18 AWG stranded bare copper conductors with polyolefin insulation, Beldfoil® shield and PVC jacket with ripcord

# **Technical Specifications**

# **Product Overview**

Environmental Space:	Indoor - Riser
Suitable Applications:	Intercom/PA Systems, Sound/Audio Systems

### **Physical Characteristics (Overall)**

#### Conductor

AWG	Stranding	Material	No. of Conductors
18	7x26	BC - Bare Copper	3
Condu	uctor Count:		
AWG	Size:		

### Insulation

Material	Nominal Wall Thickness
PP - Polypropylene	0.008 in

### Color Chart

Number	Color
1	Black
2	Red
3	White

#### **Outer Shield Material**

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Таре	Aluminum Foil-Polyester Tape w/Shorting Fold	Beldfoil®	100 %	TC - Tinned Copper	24	Solid mm

# Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness	Ripcord
PVC - Polyvinyl Chloride	0.171 in	0.017 in	Yes

# **Construction and Dimensions**

### Cabling

Lay Length	Lay Direction	Twists
2.5 in	Left Hand	4.8 twist/ft

# **Electrical Characteristics**

# Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
6.5 Ohm/1000ft	16.9 Ohm/1000ft

# Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
36 pF/ft	64.75 pF/ft

### Current

Element	Max. Recommended Current [A]
10C Temperature Rise	Per conductor @ 25°C ambient: 5 A

### Voltage

# UL Voltage Rating 300V RMS

# **Temperature Range**

UL Temp Rating:	75°C
Operating Temp Range:	-20°C To +75°C

# **Mechanical Characteristics**

Bulk Cable Weight:	24 lbs/1000ft
Max Recommended Pulling Tension:	81.2 lbs
Min Bend Radius/Minor Axis:	1.625 in

# **Standards**

NEC Articles:	800
NEC/(UL) Specification:	CMR
CEC/C(UL) Specification:	CMG
CPR Euroclass:	Eca

# **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes	
EU Directive 2003/96/EC (BFR):	Yes	
EU Directive 2011/65/EU (ROHS II):	Yes	
EU Directive 2012/19/EU (WEEE):	Yes	
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)	
EU CE Mark:	Yes	
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01	
CA Prop 65 (CJ for Wire & Cable):	Yes	
MII Order #39 (China RoHS):	Yes	

# Suitability

Suitability - Indoor:	Yes

# Flammability, LS0H, Toxicity Testing

C(UL) Flammability:	FT4
UL Flammability:	UL1666 Vertical Shaft

## **Part Number**

Plenum (Y/N):	No
Plenum Number:	6301FE

# Variants

Item #	Color	Footnote
5301FE.00305	CHROME	
5301FE 0081000	GRAY	С
5301FE 008500	GRAY	
5301FE 008U1000	GRAY	
5301FE 008U500	GRAY	

© 2018 Belden, Inc

### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS(Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be instock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product tistelf or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.