

Canare L-2T2S High-Performance Microphone Cable- 2 Conductor

Microphone & Audio Hook-Up Cable



L-2T2S

Our standard diameter 2-conductor microphone cable for general purpose audio applications. The high density braided copper shield and two inner conductors (composed of 60 thin strands of copper wire), allow for maximum flexibility and reduced handling noise. A special compound PVC outer jacket resists cracking and tears even in sub-zero environments.

L-2E5

Miniature version of L-2T2S when small size and light weight is a consideration. Useful for patch cables, hidden lavalier microphones or any balanced audio installation.

L-2B2AT

Canare's thinnest profile audio hookup wire. Amazingly flexible, with 100% foil shield, drain wire and PVC jacket that strips easily for rapid assembly. Suitable for large cable harness bundles, mixing consoles, tape machines and inter-rack wiring.



COLORS AVAILABLE						
Model	BLK	BLU	GRY	ORN	RED	YEL
L-2T2S	■	●	●	●	●	●
L-2E5	■					
L-2B2AT	●	■				

☐ = Standard Stock ☐ = Special Order

MECHANICAL SPECIFICATIONS											ELECTRICAL PERFORMANCE						
Model	Standard Length	Wgt. Stand. Lngth.	Nom. O.D.	PVC Jacket Nom. Thick.	Brittle Point	No. of Cond.	Insul. Type * Thick	Cond. AWG (Qty./mil) Cross Sec. Area (mil ²)	Pitch Twist Quad	Shield Coverage	Cond. D.C.R.	Shield D.C.R.	Nom. Cap. **	Nom. Cap. ***	Nom. Imp.	Nom. Atten.	Group Delay Time
		lbs (kgs)	Inch (mm)	Inch (mm)	°F (°C)		mil		inch (mm)		Ω/1000ft (Ω/100m)	Ω/1000ft (Ω/100m)	pF/ft (pF/m)	pF/ft (pF/m)	Ω	V/1000ft (V/100m)	mV/1000ft (mV/100m)
L-2T2S	656ft 200m	20 9	.236 6.00	.059 1.0	-56 -49	2	IPE 19.7	AC-#23 60/3.15 465	<0.79 <20	>94% TAC Braid	<19.8 <6.5	<9.4 <3.1	22 70	33 106	88	0.9 0.3	1.83 6.00
L-2E5	656ft 200m	20.2 9	.181 4.6	.035 0.9	-56 -49	2	IPE	AC-#26 30/3.15 322.5	<0.79	>96.7%	<38.7 <12.7	<6.7 <2.2	—	—	—	—	—
L-2B2AT	656ft 200m	6 3	.126 3.2	.012 0.3	-13 -25	2	IPE 12.6	AC-#25 16/4.73 279	<0.99 <25	100% Alum. Tape ****	<31.9 <10.5	—	23 73	37 120	—	—	—
	1640ft 500m	15 7															

* Dielectric Strength = 500V AC / 1min. Insulation resistance/3Mft = >1000MΩ. ** Capacitance between conductors.

*** Capacitance between conductors to shield. **** Drain Wire #22 AWG.